



DISOLVER UNIVERSAL

GENERAL USE SOLVENT

ISO 9001
BUREAU VERITAS
Certification



COD.FICHA:	FT-4200014-1
Nº EDICIÓN:	01
Nº REVISIÓN:	01
FECHA VIGOR:	10/2012

Description:

DISOLVER UNIVERSAL is a solvent/thinner of general use for paintings and lacquers.

Technical data:

Composition:	Mixing of organic solvents
Packaging:	1, 5, and 25 lt.
Appearance:	Liquid
Colour:	Transparent

Properties:	Value:	Unity:	Standard:
Brookfield Viscosity: (23°C, R2-10rpm)	<50	mPa·s	UNE-EN 12092
Density at 23°C:	0,85 ± 0,02	g/cm ³	UNE-EN 542

Source: Laboratory tests.

Uses and Applications:

Solvent or thinner used for adjusting viscosities in nitrocelulosic lacquers, synthetic varnishes or contact adhesives. It can be also used for cleaning equipments .

Instructions for use:

To get a better performance of the product, immerse the parts at least during 24 hours.

Security and hygiene:

Disolver universal is a product classified as harmful and highly flammable according to European Directive 199/45/EU
For further information, please request safety data sheet.

Storage:

Keep away from direct sunlight, heat sources and ignition points in a well ventilated and fresh environment at a temperature between +5 and +35°. Pot- life, 12 months after manufacture date.

Note:

The technical information provided by QS ADHESIVES & SEALANTS, S.L., either verbally or in writing is based on our present knowledge and is given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved.

The user is obliged to ensure that our products are suitable for the process and the use in question.

In any case our liability is limited to the value of goods supplied by us and used by you. We provide products with consistent quality, according to our general conditions of sale and distribution